

Ventura IR 35 Ceramic

- 2 ply PET film
- GPS and radio signal friendly
- Scratch-resistant surface coating
- Pressure-sensitive adhesive
- 99% UV-Rejection
- 90% IR Heat Rejection
- Optical clarity
- Excellent Manufacturing Quality
- 14-year limited warranty
- Fuel economy by reducing Air-Conditioning
- With ABG Certificate for Europe



EC-FRIENDLY



| | | |
|------------------------------|--------|-------|
| Thickness Of Film | T | 2 MIL |
| Visible Light Transmittance | VLT | 41% |
| Visible Light Reflectance | VLR | 9% |
| Solar Energy Transmittance | SET | 21% |
| Solar Energy Reflectance | SER | 8% |
| Solar Energy Absorbance | SEA | 71% |
| UV - Transmittance | UVT | <1 |
| Total Solar Energy Rejection | TSER | 59% |
| Solar Heat Gain Coefficient | g-Wert | 0,41 |
| Shading Coefficient | SC | 0,47 |
| NIR Blocking at 1025 nm | NIR | 90% |
| Glare Reduction | GR | 55% |

Disclaimer : The Performance data reported on this page was tested at DSET Lab & MATRIX Lab, USA ASHRAE, ASTM & AIMCOL Standards. All value as applied to 1/8 inch (3mm) glass. Tests are representative of actual product sample & may vary from batch to batch.

+

