

Ventura IR 50 Ceramic

- 2 ply PET film
- GPS and radio signal friendly
- Scratch-resistant surface coating
- Pressure-sensitive adhesive
- 99% UV-Rejection
- 90% IR Heat Rejection
- Optical clarity
- Excellent Manufacturing Quality
- 14-year limited warranty
- Fuel economy by reducing Air-Conditioning
- With ABG Certificate for Europe



EC-FRIENDLY



Thickness Of Film	T	2 MIL
Visible Light Transmittance	VLT	51%
Visible Light Reflectance	VLR	8%
Solar Energy Transmittance	SET	25%
Solar Energy Reflectance	SER	8%
Solar Energy Absorbance	SEA	67%
UV - Transmittance	UVT	<1
Total Solar Energy Rejection	TSER	56%
Solar Heat Gain Coefficient	g-Wert	0,44
Shading Coefficient	SC	0,50
NIR Blocking at 1025 nm	NIR	90%
Glare Reduction	GR	44%

Disclaimer : The Performance data reported on this page was tested at DSET Lab & MATRIX Lab, USA ASHRAE, ASTM & AIMCOL Standards. All value as applied to 1/8 inch (3mm) glass. Tests are representative of actual product sample & may vary from batch to batch.

+

